


Boxer

Fully equipped, complete series to vacuum pack many different food products of all shapes and dimensions. Boxer table-top models ensure an easy and secure vacuum packaging process. With the unique possibility to store your settings in the 10-program memory, standard on every Boxer table-top model.

Boxer



BOXER 35



PUMP CAPACITY 16 m³/h

MACHINE CYCLE 15–35 sec

CHAMBER DIMENSIONS

370 x 350 x 150 mm

MACHINE DIMENSIONS

550 x 450 x 405 mm

SEAL BAR 350 mm

WEIGHT 52 kg

VOLTAGE 230V–1–50Hz

POWER 0,55 kW

STANDARD

TIME CONTROL, DOUBLE/CUT-OFF/

WIDE SEAL (8 mm), SOFT AIR


OPTIONS

SENSOR CONTROL,

LIQUID CONTROL, ACS,

GAS FLUSH, 1–2 CUT-OFF SEAL

BOXER 42



Optional: ACS
with label printer

PUMP CAPACITY 21 m³/h

MACHINE CYCLE 15–35 sec

CHAMBER DIMENSIONS

370 x 420 x 180 mm

MACHINE DIMENSIONS

530 x 490 x 440 mm

SEAL BAR 420 mm

WEIGHT 64 kg

VOLTAGE 230V–1–50Hz

POWER 0,75 – 1,0 kW

STANDARD

TIME CONTROL, DOUBLE/CUT-OFF/

WIDE SEAL (8 mm), SOFT AIR

OPTIONS

SENSOR CONTROL, LIQUID

CONTROL, ACS, GAS FLUSH,

1–2 CUT-OFF SEAL, 2ND SEAL BAR


“Nothing comes
close to the
reliability and
ease of use of
Henkelman’s
Boxer series.”

Boxer




BOXER 42XL

Standard



Option



PUMP CAPACITY 21 m³/h

MACHINE CYCLE 15-35 sec

CHAMBER DIMENSIONS

460 x 420 x 180 mm

MACHINE DIMENSIONS

615 x 490 x 440 mm

SEAL BAR 420 mm

WEIGHT 72 kg

VOLTAGE 230V-1-50Hz

POWER 0,75 - 1,0 KW

STANDARD

TIME CONTROL, DOUBLE/CUT-OFF/

WIDE SEAL (8 MM), SOFT AIR

OPTIONS

SENSOR CONTROL, LIQUID

CONTROL, ACS, GAS FLUSH,

1-2 CUT-OFF SEAL, 2ND SEAL BAR

BOXER 42XL BI-ACTIVE

Standard



PUMP CAPACITY 21 m³/h

MACHINE CYCLE 15-35 sec

CHAMBER DIMENSIONS

460 x 420 x 120 mm

MACHINE DIMENSIONS

620 x 490 x 450 mm

SEAL BAR 420 mm

WEIGHT 72 kg

VOLTAGE 230V-1-50Hz

POWER 0,75 - 1,0 KW

STANDARD

TIME CONTROL, BI-ACTIVE SEAL,

SOFT AIR

OPTIONS


SENSOR CONTROL, LIQUID

CONTROL, GAS FLUSH, ACS, ESD

(ONLY FOR NON-FOOD)

BOXER 52/62

B52 Standard



B62 Standard



With ACS

PUMP CAPACITY 21 m³/h

MACHINE CYCLE 15-35 sec

CHAMBER DIMENSIONS

410 x 520 x 180 mm (B52)

360 x 620 x 180 mm (B62)

MACHINE DIMENSIONS

530 x 700 x 440 mm

SEAL BAR 410 mm (B52),

620 mm (B62)

WEIGHT 81 kg

VOLTAGE 230V-1-50Hz

POWER 0,75 - 1,0 KW

STANDARD

TIME CONTROL, DOUBLE/CUT-OFF/

WIDE SEAL (8 MM), SOFT AIR

OPTIONS

SENSOR CONTROL, LIQUID

CONTROL, ACS, GAS FLUSH,

1-2 CUT-OFF SEAL

The chamber dimensions listed refer to the usable space in the vacuum chamber (length x width x height). The machine dimensions listed refer to length x width x height. Other voltages available. Textual and printing errors reserved

