Breville | PolyScience

the HydroPro™ Plus CSV750 240V

Consistent, repeatable results

The **HydroPro™ Plus** initiates a new generation of professional sous vide immersion circulators. Featuring Sous Vide Toolbox™, an intuitive on-board guided cooking experience that simplifies sous vide cooking by using scientific algorithms to calculate time to temperature and pasteurization for a vast range of foods.

The HydroPro™ Plus includes a digital needle probe that displays the core temperature of the food in real-time, enabling delta cooking. Data is stored on-board and can be transferred to the HACCP Manager App via Bluetooth for easy logging of all your sous vide cooks.

Programming and repeatability of your cooks is made simple thanks to 'My Presets' and usability has been enhanced via a large touch screen that allows easy manual input of cooking parameters. The powerful heater and newly designed pumping system ensure precise temperature control across a wide range of cooking volumes.

Designed with food safety and simple maintenance in mind, the design features a smooth waterproof construction, quick-release clamp, and a magnetic impeller for easy cleaning and descaling. Removable parts are commercial dishwasher safe.

Visit **www.sousvideaustralia.com** to learn about the entire line of Breville | PolyScience products and great recipe ideas.

Sous Vide Immersion Circulator

Technical Specifications

PERFORMANCE		
Power	1485 Watts	
Flow Rate	17 L/Min	
Max Water Bath Size	45L with lid	
DURABILITY		
• IPX7 Water Resistant • NSF and IEC Commercially Certified	• Stainless Steel Exterior • Ruby Bearing • Tungsten Carbide Shaft	
PRECISION		
Temperature Resolution	0.1°F/0.1°C	
Temperature Stability	± 0.1°F/0.1°C	
Maximum Water Temperature	194°F/90°C	
USABILITY		
Color TFT Touch Display On-board Cooking Guide Sous Vide Toolbox™ Manual Time & Temperature Controls Integrated Digital Probe Variable Flow Speed	360° Adjustable Flow Direction Coil-less Heating Chamber Low Water Detection Magnetic Impeller Coupling Adjustable & Detachable Clamp	
CONNECTIVITY		
Bluetooth		
WEIGHTS & DIMENSIONS		
Unit Weight	4.4lb / 2kg	
Unit Dimensions (L x D x H)	14.6in x 3.7in x 6.7in / 37.1cm x 9.3 x 17cm	
Shipping Weight	7.1lb / 3.2kg	
Shipping Dimensions (L x D x H)	16.3in x 5.8in x 9.9in / 41.5cm x 14.7cm x 25.2cm	
SKU Number	CSV750PSS4JAN1 CSV750PSS4GHK1 CSV750PSS4EAN1	Australia/New Zealand Hong Kong South Korea
ACCESSORIES	Adjustable & Detachable Clamp Magnetic Impeller 360° Adjustable Flow Direction Foot Digital Probe & Calibration Holder Carry Case with Handle.	